

PIN ASSIGNMENT

HDMI 19M(A)	HDMI 19M(C)	
1	2	TMDS Data2+
3	3	TMDS Data2-
2	1	TMDS Data2 Shield
4	5	TMDS Data1+
6	6	TMDS Data1-
5	4	TMDS Data1 Shield
7	8	TMDS Data0+
9	9	TMDS Data0-
8	7	TMDS Data0 Shield
10	11	TMDS Clock+
12	12	TMDS Clock-
11	10	TMDS Clock Shield

PIN ASSIGNMENT

HDMI 19M(A)	HDMI 19M(C)	
13	14	CEC
15	15	SCL
16	16	SDA
18	18	+5V Power
14	17	Reserved
19	19	Hot Pulg detect
17	13	DDC/CEC Ground
Shell	Shell	





ROHS Compliant

NO	Descriptron	Q'TY	Unit
4	65P Black PVC		
3	HDMI AF,BLACK INSULATION,SHELL 3U" GOLD PLATED WITH SOLDER(P/N YQT-HCM3)		
2	HDMI AM,BLACK INSULATION,SHELL 3U" GOLD PLATED WITH SOLDER(P/N YQT-HAM3)		
1	(1P*30AWG+D+AL)*5C+4C*30AWG+AL+D+B OD5.5 L=6ft Black		

www.USBFireWire.com

Tolerance, Unless Otherwise Specified	
UP TO 5	±0.2
ABOVE 5 —30	±0.3
ABOVE 30—50	±0.4
ABOVE 50	±0.5
ANGLE	±3°

DRAW:		TITLE	HDMI AM TO CM		
CHEDKED:		PART NO.	RR-5D-3S-XXG		
APPROVED:		DRAW NO.			
DATE	2012-9-18	SCALE	1:1	UNIT	mm