



4546

P1	P2
1	3
3	5
2	4
4	6
6	8
5	7
7	9
9	11
8	10
10	12
12	14
11	13
14	2
19	1
17	16
13	15
15	17
16	18
18	19
SHIELD	SHIELD

NOTE: All relevant materials are complied with RoHS directive .

3	PCB MSL-62	1	M723
	COPPER FOIL 20*65mm	1	M583
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC BLACK		M304
2	HDMI 19 D MALE, GOLD FLASH ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR (1170-2A002-101)	1set	M943
1	HDMI 19 FEMALE GOLD FLASH ON CONTACTS & GOLD FLASH ON METAL HOOD, BLACK INSULATOR	1set	M363
No.	DESCRIPTION	Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm	
CHECKED	HU		
DRAWING	JIANG		
DATE	26/APR/11		
ITEM NO.	RR-HDMI-AFDM	UNIT:mm	

www.USBFireWire.com