

1

2

3

4

Notes: (Unless Otherwise Specified)

1. Waterproof Rate: IP68.
2. Recommend Panel Thickness: 0.8 to 4.0 mm.
3. Recommend Torque: 9.0~10.0 Kgf-cm.
4. Mating Cap P/N: GT1C5221X2.
5. RoHS Compliant.
6. 產品採用USB 10PCS吸塑盒包裝;並於吸塑盒上蓋貼上標籤.

RR-152200-11100\_REV:XX\_QTY:10PCS

LOT: XXXX

Made in China

7. 標籤上的REV: 請依照成品圖面版本.

GTC  
DOC.CENTER.ISSUE  
OCT.01.2019  
ONLY FOR  
RELEASE

Recommend  
Panel Cut-Out

Recommend PCB Layout  
Scale 2:1

Item	Part Name	Material/Finish	Q'ty
5	Glue	Epoxy Color: Black	
4	Gasket	Silicone Color: Black	1
3	Hex Nut	Thermoplastic Color: Black	1
2	Contacts	Copper Alloy Finish: Au Plated	10
1	Housing	Thermoplastic Color: Black	1

TITLE	DRAWING NUMBER	REV.
C2 2A 10P Panel Female Dip Lock	RR-152200-11100	01

THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES	UNIT	SHEET
	B	1:1	Lucas 10/01/19	Lucas 10/01/19	Ray 10/01/19	X.X ± 0.5 X.XX ± 0.2	mm	1/1

TOLERANCES	UNIT	SHEET
X.X ± 0.5 X.XX ± 0.2	mm	1/1

USB FIREWIRE.com

THE INFORMATION CONTAINED HEREIN IS THE PROPRIETARY INFORMATION OF RR BUSINESS VENTURES, LLC. THE POSSESSOR AGREES TO THE FOLLOWING

1. MAINTAIN THIS DOCUMENT IN CONFIDENCE
2. NOT TO REPRODUCE OR COPY IT
3. NOT TO REVEAL OR PUBLISH IT IN WHOLE OR IN PART

COPYRIGHT © 2019

1

2

3

4