



PINOUT			
P1		P2	
1	—————	1	RED 24#
2	⌢	2	WHITE
3	⌢	3	GREEN
4	—————	4	BLACK 24#
SHIELD	—————	SHIELD	

NOTE: All relevant materials are complied with RoHS directive .

5	BLACK HEAT SHIRK TUBE ϕ 1.0*10mm	A4HA23-0959	1	M959
	MOLDED PE COLOR TRANSPARENT	A5BA02-0280		M280
	MOLDED PVC (SEE LIST)	H1BF01-0304		M304
4	MOLDED PVC (SEE LIST)	H1BF01-0304		M304
3	USB 2.0 CABLE, UL STYLE 1 TWISTED PAIR 28AWG AND 2C 24AWG,AMA BRAID OD 4.5mm, JACKET (SEE LIST), DRAWING No.EUAB2801P2402C-139	H5KH29-0304	L-20mm	M304
2	USB A FEMALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR	A1HC21-0108	1	M108
1	USB A MALE, GOLD FLASH ON CONTACTS, WHITE INSULATOR, SHORT PIERCE TYPE	A1HA49-0108	1	M108
No.	DESCRIPTION		Q'TY	Supplier
APPROVED		 USB FIREWIRE.com	Cable Length Unless Other Spec. Tolerances:	
CHECKED	HU		0 ~200mm	±10mm
DRAWING	MEI		201~1000mm	±20mm
DATE	16/JUN/12	ITEM NO.	RR-USB2-XX-AA-EXT	UNIT:mm
	CHECKED			 